


STONECREST™ SLATE

STEEL SHINGLE

PRODUCT DATA



Manufactured in Joplin, MO

METALWORKS® STONECREST™ SLATE is made of heavier gauge steel and has been double stamped for a more dramatic slate look that closely replicates the random finish of natural slate. Available in a beautiful array of colors.

USES

For application to roof decks with inclines not less than 3 inches per foot and up to mansard or side-wall application. For slopes between 3 and 4 inches per foot, TW Metal & Tile Underlayment must be used over entire deck area.**

ADVANTAGES

- Backed by a 50 Year Limited Product Warranty, 25 Year Full Start Period, Limited Transferability, a 30 Year Finish Limited Warranty, and a 50 Year Limited Wind Warranty against damage from winds up to 110 mph. See Limited Warranty for details.
- Galva-Strength G-90 steel construction.
- Special coating process resists dirt and environmental aging. Fluoropolymer coating system from The Valspar® Corporation with Kynar® 500/Hylar 5000® coating.
- Lightweight compared to traditional roofing products.
- Resists fading and chalking.
- Fire resistant for added protection.**
- Can be applied over existing asphalt shingles eliminating disposal cost and mess.***
- Four-way locking system for enhanced performance.

COLORS

StoneCrest Slate Colors:


- Quaker Green
- Sierra Slate Grey
- Vermont Blue
- Sequoia Red

CERTIFICATION

UL Standard 2218, Class 4	ICC-ES Legacy Report No. 5484
ASTM D3161, (modified to 110 MPH)	ICC-ES Legacy Report No. 586
UL Class A Fire Rating**	Accepted for Use
CCMC 13011-R	City of New York
	Department of Buildings MEA 156-00-M Vol II

PRODUCT DATA*

Shingle Size	12-5/8" x 39-3/4"
Exposure	12"
Coverage per Box	49.2 sq ft (approx. 1/2 sq)
Shingles per Box	15
Shingles per Square	30
Weight per Shingle	2.5 lbs
Weight per Square	74 lbs



Shingle/Accessory material: Nominal 0.0162" thickness, including G-90 galvanization and paint coatings. Exterior finish is fluoropolymer (PVDF) with anti-corrosive primer, 1 mil dry film thickness. Interior finish is a wash coat with anti-corrosive primer, 0.6 mil dry film thickness.

Clip: 1-1/4" wide x 2-1/8" long x 1/5" deep

Clip Material: 0.015" thick, G-90 galvanized steel

Refer to Accessory Product Data Sheet for more information.

*All values stated as nominal

**Contact TAMKO for U.L. Class A assembly requirements.

***Check your Local Building Code. Building Code restrictions may apply.

Visit our Web Site at www.tamko.com or www.metalworksroof.com

9/2004



METALWORKS® and TAMKO® are registered trademarks of TAMKO® Roofing Products, Inc. Fluoropon® and Valspar® are registered trademarks of The Valspar Corporation, Inc. Kynar® is a registered trademark of ATOFINA Chemicals, Inc. Hylar 5000® is a registered trademark of Solvay Solexis, Inc. Stonecrest™ is a trademark of TAMKO® Roofing Products, Inc.

Central District	220 West 4th St., Joplin, MO	64801	800-641-4691
Northeast District	4500 Tamko Dr., Frederick, MD	21701	800-368-2055
Southeast District	2300 35th St., Tuscaloosa, AL	35401	800-228-2656
Southwest District	7910 S. Central Exp., Dallas, TX	75216	800-443-1834
Western District	5300 East 43rd Ave., Denver, CO	80216	800-530-8868